

# FEEDER

### WR FEEDER



WR FEEDER is a friction feeder for flat sheets, cards, and coupon, available in 3 versions.

Thanks to its stepper motor, it can reach a feed speed up to 60 meters/minute.

The feed selection uses rubber counterrotating rollers with micro adjustments on both the left and right side, which make the **feeder extremely flexible for any type of product**. The 300 mm high loading unit, equipped with minimum load capacity control, guarantees a great working autonomy. **WR FEEDER** is controlled by a microprocessor which uses an **LCD display keypad with two 20-character rows and 7 function keys** to interface with the user. Through this, it is possible to set all the working parameters, such as continuous feed or multiple copies on demand, feeding speed, stop delay, print delay and stroke counter.



## **TECHNICAL FEATURES**

### **WR FEEDER**

#### Friction feeder for flat sheets, cards and coupons

#### Available models

#### \*WR/250

Product width: Product width : Product thickness: Product thickness : Feeding speed: Drive: Power supply: Power consumption: Dimensions : Weight :

#### \*WR/400

Product width: Product width : Product thickness: Product thickness : Feeding speed: Drive: Power supply: Power consumption: Dimensions : Weight :

#### \*WR/500

Product width: Product width : Product thickness: Product thickness : Feeding speed: Drive: Power supply: Power consumption: Dimensions : Weight : 60 x 60 mm min. 250 x 300 mm max 0,20 mm min. 10,00 mm max up to 60 m/min. stepper motor 230 Vac, 50 Hz 300 W 891 x 413 x h. 490 35 Kg.

60 x 60 mm min. 400 x 300 mm max 0,20 mm min. 10,00 mm max up to 60 m/min. stepper motor 230 Vac, 50 Hz 300 W 891 x 563 x h. 490 40 Kg.

60 x 60 mm min. 500 x 300 mm max 0,20 mm min. 10,00 mm max up to 40 m/min. stepper motor 230 Vac, 50 Hz 300 W 891 x 662 x h. 490 45 Kg. LABEL ENGINEERING Srl Via Bernardino Zenale 19 20024 Garbagnate Milanese (MI) Italy tel. +39 02 99021148 fax +39 02 99022613

info@label-engineering.it www.label-engineering.it

- \* Available in two versions:
- Standard output terminal
- Oversized output terminal suitable for the integration of marking or labeling systems

Label Engineering reserves the right to make construction changes without prior notice that may lead to changes in the characteristics or performances indicated.